



PFAFF

Bag

ClassicStyle Quilt¹⁵²⁷

Size 31 x 37 cm (12" x 14.5")

You need:

- 80 cm (32")
Dark red batik fabric for piecing and lining
- 10 cm (4")
Purple batik fabric for piecing
- 20 cm (8")
White batik fabric for piecing
- 10 cm (4")
Pink patterned fabric for piecing
- 10 cm (4")
Dark pink patterned fabric for piecing
- 100 cm (39")
Black fabric for edges and shoulder strap
- 40 cm (16") Batting
- 8 m (8 7/8 yds)
Fusible black bias tape, 6 mm (1/4")
- Embroidery stabilizer
- Fusible interfacing
- Matching sewing thread in light pink, dark red and black
- Machine embroidery thread, dark grey
- Black zipper, 30 cm (12")
- Fabric marker
- Rotary cutter, cutting mat and ruler
- Safety pins
- 1/4 inch Quilting foot
- Zipper foot
- Quilt needle



1 Cutting

6 mm (1/4 ") seam allowance included

Dark red batik

- 10 pieces – 9 x 9 cm (3 1/2" x 3 1/2") piecing
- 3 pieces – 9 x 16.5 cm (3 1/2" x 6 1/2") piecing
- 1 piece – 30.5 x 65 cm (12" x 24") back/flap lining
- 1 piece – 30.5 x 38 cm (12" x 15") front lining
- 1 piece – 16.5 x 26 cm (6 1/2" x 10") inner pocket

Purple batik

- 5 pieces – 9 x 9 cm (3 1/2" x 3 1/2") piecing

White batik

- 6 pieces – 9 x 9 cm (3 1/2" x 3 1/2") piecing
- 5 pieces – 9 x 16.5 cm (3 1/2" x 6 1/2") piecing

Pink print

- 10 pieces – 9 x 9 cm (3 1/2" x 3 1/2") piecing

Dark pink print

- 5 pieces – 9 x 9 cm (3 1/2" x 3 1/2") piecing

Black solid

- 8 strips – 2.5 cm (1") edges
- 1 strip – 8 x 97 cm (3" x 38.5") shoulder strap

Fusible Interfacing

- 1 piece – 4 x 95 cm (1 1/2" x 37 1/2")

Batting

- 2 pieces – 33 x 39.5 cm (13" x 15 1/2") front and back
- 1 piece – 25.5 x 39 cm (10" x 13") flap

2 Sewing

- Refer to the layout designs for the placement of the piecing squares and rectangles. You will have a front, back and flap layout.
- Attach the 1/4" quilting foot to your ClassicStyle Quilt sewing machine. Thread your sewing machine with neutral cotton sewing thread on the top and in the bobbin. Sew the front, back and flap according to the layout using a straight stitch with a 6 mm (1/4") seam allowance. Stitch the squares and rectangles in rows from left to right. It's important to be sure that the seam allowance is 6 mm (1/4"), otherwise the squares won't fit together or the bag will change size. Press the seam allowance to the dark coloured fabric. Sew the rows together as per layout.
- Press the fusible bias tape over the ditches (seam lines). Start with the diagonals and then follow with the verticals and finish with the horizontal seams. Place the pieced front, back and flap on the corresponding batting and pin. Place the embroidery stabilizer under the quilt/batting piece and sew with dark grey embroidery thread one of the beautiful quilt stitches from your ClassicStyle Quilt machine to secure the bias tape. Tear-away the stabilizer after decorative stitching is complete.
- Sew the shoulder strap. Press fusible interfacing in the middle of the strip. Fold the strip in half lengthwise with right sides facing. Sew together with a 2 cm (3/4") seam allowance with a straight stitch. Leave the short edges open. Turn right side out and press.
- Sew the zipper in between the back piece and the flap piece. Trim the seam allowance from batting before sewing. Place the zipper right sides together with the flap. Place the lining for the inside pocket on the other side of the zipper (right side of the lining together with wrong side of the zipper).

Change presser foot to the zipper foot and sew with a straight stitch near the zipper. Turn right side out and press. Pin the ends of the shoulder strap on the top corners of the back piece. Place the other part of the zipper on the top of the back piece (over the edges of the shoulder strap) with right sides together. Sew with a straight stitch near the zipper, turn right side out and press.

- Sew the edges on the back/flap. Place the black strips lengthwise right sides together with the quilted back/flap. Sew together with a straight stitch and press seam allowance to the edges. (Still use the Zipper foot so you easily can pass the zipper.) Change presser foot to ¼ inch Quilt foot and sew the upper and lower edges.
- Sew the edges on the back/flap lining. Place the black strips lengthwise right sides together with the lining. Sew together with a straight stitch and press seam allowance to the edges. Repeat with the upper edge.
- Sew the inside pocket on the back/flap lining. Fold the upper edge of the inside pocket twice 1,5 cm (5/8"). Press and stitch. Press seam allowance 1 cm (3/8") along the other 3 sides. Place the pocket as shown and stitch.
- Place the front lining right sides together with the quilted front. Sew together along the top edge with a straight stitch. Press seam allowance apart.
- Sew the edges on the front/lining. Place the black strips lengthwise right side together with the quilted front/lining and sew together with a straight stitch. Press seam allowance to the edges. Repeat with the lower edge at the quilted front. Fold the lining to the inside and press.

- Sew the front and back together. Place the quilted front right side together with the back/flap. Make sure that the squares and tape match. Sew together with a straight stitch. The black edges will measure 1 cm (3/8") when finished. Place the back/flap lining right sides together with the back/flap and front lining. Sew all three layers together with a straight stitch (lengthwise and along the upper edge). Turn right side out.
- Stitch in the ditch between the quilt and the black edge. Make sure the fabric for the front and back linings are inside the lower edge to close the inside of the bag.
- Sew the back/flap lining together with the zipper. Change to the Zipper foot and sew a straight stitch near the back quilt on the zipper back.



